



Perm State University
Bukireva Str. 15, 614990, Perm, Russia

Ontology-Driven Automation of IoT-Based Human-Machine Interfaces Development

Konstantin Ryabinin

e-mail: kostya.ryabinin@gmail.com


Svetlana Chuprina

e-mail: chuprinas@inbox.ru

Konstantin Belousov


e-mail: belousovki@gmail.com

Custom Hardware Human-Machine Interface?



Virtual Reality

Custom Hardware Human-Machine Interface?




Virtual Reality



Simulators


Custom Hardware Human-Machine Interface?



Virtual Reality




Simulators



**Complex Data
Analytics**


**Custom Hardware
Human-Machine Interface?**



Virtual Reality



Simulators




Complex Data Analytics

Custom Hardware Human-Machine Interface?




**Human-Centric
IoT**



Virtual Reality



Simulators



Complex Data Analytics


Custom Hardware Human-Machine Interface?




**Human-Centric
IoT**




**Interactive
Exhibits**





*“We only have two demands!
Why don't people just give us what we want?”*


**Enrich, not replace
existing digital infrastructure**





© TimoElliott.com

*“We only have two demands!
Why don't people just give us what we want?”*

- 1. Increase the level of HMI development tools**
- 2. Propose the approach of smart systems building to automate:**
 - 2.2. IoT devices firmware generation**
 - 2.3. Middleware generation**
 - 2.4. Using IoT devices as HMI to steer third-party software**
- 3. Create the smart system according to the proposed approach**
- 4. Test smart system as a middleware to marry custom IoT-based HMI with third-party software**











Multiplatform client-server adaptive scientific visualization system SciVi

Ryabinin, K., Chuprina, S.: Development of Ontology-Based Multiplatform Adaptive Scientific Visualization System. Journal of Computational Science 10, 370–381 (2015). <https://doi.org/10.1016/j.jocs.2015.03.003>





HMI




3rd-Party Software



Data Link




Control Link





ONTOLIS Ontology Editor

➡ Data LINK

➡ Control LINK



HMI




3rd-Party Software





Data Link





Control Link







HMI




3rd-Party Software





Data Link





Control Link







HMI




3rd-Party Software





Data Link





Control Link
















HMI




3rd-Party Software




Data Link



Control Link




HMI





Data Link





Control Link













HMI



Keynote




3rd-Party Software




Data Link





Control Link





HMI




3rd-Party Software




Data Link





Control Link





HMI




3rd-Party Software





Data Link



Control Link





 **Data Link**  **Control Link**

Task:

Discover relationships between **psychological characteristics** of social network users and their **verbal behavior**

Instruments:

1. Semograph computer linguistics system
2. SciVi visual analytics system

Data:

1. 18'000 posts from VKontakte social network made by 800 users
2. Big Five personality traits (psychological profiles) of these users:
 - 2.1. **O**penness
 - 2.2. **C**onscientiousness
 - 2.3. **E**xtraversion
 - 2.4. **A**greeableness
 - 2.5. **N**euroticism

Preprocessing:

Correlation analysis resulting in the graph where psychological characteristics are connected with verbal patterns

Verbal behavior patterns are classified into semantic groups

HMI: Use gestures to activate groups with specific spatial semantics

▼ Data Sources


- Glove

▼ Filters


- Classifier
- Gesture Up
- Gesture Down
- Gesture Left
- Gesture Right

▼ Visual Objects

- BFI Graph



Visualize



What we have:

1. Approach to building ontology driven smart systems for automating hardware HMI creation
2. Single smart system with high-level graphical toolset to
 - 2.1. Program
 - 2.2. Debug
 - 2.3. Monitor} hardware HMI
- 2.4. Create middleware to steer 3rd-party systems (including legacy ones)
3. Perceptive-cognitive HMI for multimodal analytics

What we plan:

1. Tackle problems of transforming M2M IoT systems into Human-Centric ones
2. Create IoT-based healthcare monitoring systems
3. Create HMI for virtual reality applications



Perm State University
Bukireva Str. 15, 614990, Perm, Russia

Thank You for Attention!

Konstantin Ryabinin

e-mail: kostya.ryabinin@gmail.com

Svetlana Chuprina

e-mail: chuprinas@inbox.ru

Konstantin Belousov

e-mail: belousovki@gmail.com